

COMPLETE LIME-BASED SYSTEM · 10 TO 200 M²

PURE Microcement Kits

 Complete lime-based system pre-dosed for the whole project, from 10 to 200 m²

 10 to 200 m²

33 PURE colours

Lime-based

2 to 3 mm

5-year material warranty

Description and use

KCberry PURE Microcement Kits bring together the complete lime-based system of the PURE line, pre-dosed for the project area. A seamless, jointless 2 to 3 mm coating applied over existing tiles, concrete or render, with the artisan finish of lime. You choose the finish (PURE Finishing or PURE Traffic), the colour from 33 PURE shades and the sealer sheen. **5-year warranty on the material.**

Composition by area — 10 to 60 m²

Component	10 m ²	20 m ²	30 m ²	40 m ²	50 m ²	60 m ²
Adhesion Promoter (5 L)	1	1	2	2	2	3
50 g fibreglass mesh	10 m	20 m	30 m	40 m	50 m	60 m
PURE Base (20 kg)	1	2	3	4	5	6
PURE Finishing or Traffic	1	1	3	3	4	4
PURE Pigment	1	1	3	3	3	4
Lime Resin	2 × 5 L	1 × 25 L	2 × 25 L	2 × 25 L	3 × 25 L	3 × 25 L
Lime Sealer (4+2 L)	—	1	1	1	2	2
Lime Sealer (2+1 L)	1	—	—	1	—	—

Composition by area — 70 to 200 m²

Component	70 m ²	80 m ²	90 m ²	100 m ²	110 m ²	120 m ²	130 m ²
Adhesion Promoter (5 L)	3	4	4	4	5	5	6
50 g fibreglass mesh	70 m	80 m	90 m	100 m	110 m	120 m	130 m
PURE Base (20 kg bucket)	7	8	9	10	11	12	13
PURE Finishing (15 kg) or Traffic (18 kg)	5	5	6	7	7	8	9
PURE Pigment	5	5	6	7	7	8	9
Lime Resin	4 × 25 L	4 × 25 L	4 × 25 L	5 × 25 L	5 × 25 L	6 × 25 L	6 × 25 L
Lime Sealer (sets)	2×6 L + 1×3 L	3×6 L	3×6 L	3×6 L + 1×3 L	4×6 L	4×6 L	4×6 L + 1×3 L

Component	140 m ²	150 m ²	160 m ²	170 m ²	180 m ²	190 m ²	200 m ²
Adhesion Promoter (5 L)	6	6	7	7	8	8	8
50 g fibreglass mesh	140 m	150 m	160 m	170 m	180 m	190 m	200 m
PURE Base (20 kg bucket)	14	15	16	17	18	19	20
PURE Finishing (15 kg) or Traffic (18 kg)	9	10	11	11	12	13	13
PURE Pigment	9	10	11	11	12	13	13
Lime Resin	7 × 25 L	7 × 25 L	8 × 25 L	8 × 25 L	8 × 25 L	9 × 25 L	9 × 25 L
Lime Sealer (sets)	5×6 L	5×6 L	5×6 L + 1×3 L	6×6 L	6×6 L	6×6 L + 1×3 L	7×6 L

Finish: PURE Finishing (walls) or PURE Traffic (floors and high traffic), as chosen when ordering.

Application sequence

1	Prepare. Smooth, level, clean and degreased substrate. Apply the Adhesion Promoter.
2	Base. Apply two pigmented coats of PURE Base with a steel trowel; on floors, with fibreglass mesh.
3	Finish. Apply pigmented PURE Finishing or PURE Traffic with a steel trowel.
4	Seal. Once the coating is dry and its moisture is no higher than 5%, apply two cross coats of Lime Sealer.

Mixing ratios, consumption and times are detailed in the technical data sheets for each component, available at kcberry.ie.

Precautions

- PURE microcements are lime-based: avoid contact with eyes and skin and avoid inhaling the dust; wear gloves and safety glasses.
- Keep out of the reach of children. Dispose of packaging in accordance with current legislation.

COMPLETE KCBERRY SYSTEM · CUSTOMERS WHO BUY THIS PRODUCT ALSO BUY

KCberry Sample Kit	See the real colour before you order.
KCberry Steel Trowel	Tool for all PURE coats.
Two-Component Polyurethane Varnish	Optional maximum protection over Lime Sealer.

Need technical support for your project?

The KCberry technical team sizes your system, confirms the right substrate preparation and supports you or your contractor remotely, from order to final seal.

REQUEST A FREE QUOTE: kcberry.ie

WhatsApp / Tel. +353 21 221 0022 · info@kcberry.ie · kcberry.ie

The product must not be used for purposes other than those specified without prior written instructions. The information in this sheet is based on tests and practical experience and is given in good faith; it is the user's responsibility to take the measures needed to comply with applicable legal requirements. The Safety Data Sheet is available to professionals on request. This edition supersedes all previous ones.