

LIME-BASED MICROCEMENT · WALL FINISH

PURE Finishing KCberry

Lime-based finish with nuances, marbling and trowelled effect, for walls

Lime-based

Tadelakt effect

Walls only

Working time 1h30

 0.5 kg/m²

Description and use

PURE Finishing KCberry is the lime-based finishing microcement of the PURE line for walls. It has a more natural look than PURE Traffic, with the nuances, marbling and trowelled effect that give walls a tadelakt-like appearance — with the strength of microcement. It is always applied over **PURE Base**.

Properties and benefits

- **Soft, pleasant touch**, natural and elegant look.
- **Nuances, marbling and trowelled effect** — a visual effect similar to tadelakt.
- Sealed with Lime Sealer in matt, satin or gloss.
- **For walls only.** On floors use PURE Traffic.

Technical data

Property	Specification	Unit	Method / Standard
Type	Lime-based finishing microcement	—	—
Liquid component	Lime Resin KCberry	—	—
Mixing ratio	15 kg of PURE Finishing + 6.4 L of Lime Resin	—	—
Consumption (2 coats)	0.5	kg/m ²	—
Mortar working time	about 1h30 (varies with temperature and humidity)	—	—
Maximum moisture for sealing	5	%	—
Sealing	Lime Sealer KCberry — matt, satin or gloss	—	—
Packaging	Bucket of 15	kg	—

Mixing

Microcement	Lime Resin	Use
15 kg of PURE Finishing	6.4 L	All coats pigmented

- 1 Resin.** Pour the corresponding amount of Lime Resin into an empty container.
- 2 Pigment.** Shake the PURE Pigment and mix it with the Lime Resin until the liquid is uniform.
- 3 Microcement.** Gradually pour in the microcement, mixing mechanically for 2 to 3 minutes until a smooth paste is obtained.

Prepare only the quantity needed: after mixing you have about 1h30, depending on temperature and humidity.

Application

- 1 Base.** Apply over the completed PURE Base.
- 2 Finish.** Apply with a steel trowel. All coats must be pigmented.
- 3 Seal.** Once dry, always seal with **Lime Sealer KCberry**, with the coating at a moisture content no higher than 5%. Matt, satin or gloss finish.

Precautions

- Lime-based product: avoid contact with eyes and skin and avoid inhaling the dust.
- Wear rubber gloves and safety glasses. Keep out of the reach of children.
- Respect the expansion joints of the substrate.
- Dispose of empty packaging in accordance with current legislation.

COMPLETE KCBERRY SYSTEM · CUSTOMERS WHO BUY THIS PRODUCT ALSO BUY

PURE Base KCberry	Mandatory base layer.
Lime Resin KCberry	Liquid component (6.4 L per 15 kg).
KCberry PURE Pigment	33 mineral colours.
Lime Sealer KCberry	Mandatory sealing — matt, satin or gloss.

Need technical support for your project?

The KCberry technical team sizes your system, confirms the right substrate preparation and supports you or your contractor remotely, from order to final seal.

REQUEST A FREE QUOTE: kcberry.ie

WhatsApp / Tel. +353 21 221 0022 · info@kcberry.ie · kcberry.ie

The product must not be used for purposes other than those specified without prior written instructions. The information in this sheet is based on tests and practical experience and is given in good faith; it is the user's responsibility to take the measures needed to comply with applicable legal requirements. The Safety Data Sheet is available to professionals on request. This edition supersedes all previous ones.