

LIME-BASED MICROCEMENT · HIGH TRAFFIC

PURE Traffic KCberry

Uniform, high-strength lime-based finish for floors

Lime-based

High traffic

Floors

Working time 1h30

 1.0 kg/m²

Description and use

PURE Traffic KCberry is the lime-based finishing microcement of the PURE line with a high level of resistance, ideal for high-traffic surfaces. It has a more uniform look, with fewer nuances and less marbling than PURE Finishing. Suitable for floors and can also be used on other surfaces. It is always applied over **PURE Base**.

Properties and benefits

- **High resistance**, ideal for high-traffic surfaces.
- **Uniform look**, with fewer nuances and less marbling.
- Can be applied on floors and other surfaces.
- Sealed with Lime Sealer in matt, satin or gloss.

Technical data

Property	Specification	Unit	Method / Standard
Type	Lime-based finishing microcement	—	—
Liquid component	Lime Resin KCberry	—	—
Mixing ratio	18 kg of PURE Traffic + 6.8 L of Lime Resin	—	—
Consumption (2 coats)	1.0	kg/m ²	—
Mortar working time	about 1h30 (varies with temperature and humidity)	—	—
Maximum moisture for sealing	5	%	—
Sealing	Lime Sealer KCberry — matt, satin or gloss	—	—
Packaging	Bucket of 18	kg	—

Mixing

Microcement	Lime Resin	Use
18 kg of PURE Traffic	6.8 L	All coats pigmented

- 1 Resin.** Pour the corresponding amount of Lime Resin into an empty container.
- 2 Pigment.** Shake the PURE Pigment and mix it with the Lime Resin until the liquid is uniform.
- 3 Microcement.** Gradually pour in the microcement, mixing mechanically for 2 to 3 minutes until a smooth paste is obtained.

Prepare only the quantity needed: after mixing you have about 1h30, depending on temperature and humidity.

Application

- 1 Base.** Apply over the completed PURE Base.
- 2 Finish.** Apply with a steel trowel. All coats must be pigmented.
- 3 Seal.** Once dry, always seal with **Lime Sealer KCberry**, with the coating at a moisture content no higher than 5%. Matt, satin or gloss finish.

Precautions

- Lime-based product: avoid contact with eyes and skin and avoid inhaling the dust.
- Wear rubber gloves and safety glasses. Keep out of the reach of children.
- Respect the expansion joints of the substrate.
- Dispose of empty packaging in accordance with current legislation.

COMPLETE KCBERRY SYSTEM · CUSTOMERS WHO BUY THIS PRODUCT ALSO BUY

PURE Base KCberry	Mandatory base layer.
Fibreglass Mesh	Recommended reinforcement on floors.
Lime Resin KCberry	Liquid component (6.8 L per 18 kg).
Lime Sealer KCberry	Mandatory sealing — matt, satin or gloss.

Need technical support for your project?

The KCberry technical team sizes your system, confirms the right substrate preparation and supports you or your contractor remotely, from order to final seal.

REQUEST A FREE QUOTE: kcberry.ie

WhatsApp / Tel. +353 21 221 0022 · info@kcberry.ie · kcberry.ie

The product must not be used for purposes other than those specified without prior written instructions. The information in this sheet is based on tests and practical experience and is given in good faith; it is the user's responsibility to take the measures needed to comply with applicable legal requirements. The Safety Data Sheet is available to professionals on request. This edition supersedes all previous ones.